



Responsible: D. Rutz Tel.: (0209) 401 733 Date: 24.11.2009 Fax: (0209) 401 743



## Possible information on display in model DVC... (functions of electronic)

Display	What does it mean?	Activation	Disactivation
Letter E	E - like error. Can be shown only when alu/metal filters are out.  Function is connected with safety system. It is to avoid possibility to operate the hood when the filters are not inside.  If a filter is not in place - letter E will be shown, and the system will cut off the power from the motor which is controlling the hood.	It is activated automatically, after dismantling the metal/aluminum filter.	Install the filter again.     Press and hold Timer button for more than 5 sec.     E will disappear.     Now press plus key sto unlock the system - after it normal work is possible.
Letter A	A means that the hood is in automatic mode. DVC hoods give user a possibility to work automatically (without control from user).  A smelling sensor, located in the bottom part of the hood, (just behind the LED lights) will check the air, each 30 sec., and compare it to "zero" condition - memorized after first connection to the supply net. If/ when it will detect impurities, it will start at a level that allows to remove it effectively.	Press and hold the minus key - for more than 2 sec. (when fan is in position 0).	Press and hold the minus key - for more than 2 sec. (at any level).
Letter F	F - like filter. This letter appears, when aluminum filter should be cleaned.  NOTE: It is possible to operate the hood when F is shown on the display, however, the user will not see the speed on the display.	It is activated automatically. Pro- gram will count total 100 hours, starting from first use.	<ol> <li>Take off the alu filter and clean it.</li> <li>Install the filter again.</li> <li>Press and hold Timer key for more then 10 sec. F letter will disappear.</li> </ol>
Letter C	C - like carbon. This letter appears, when the carbon filter should be changed.  NOTE: It is possible to operate the hood when C is shown on the display, however, the user will not see the speed on the display.  NOTE: Program does not recognize if user is using the carbon filter or not. Function is automatically activated.	It is activated automatically. Program will count total 100 hours, starting from first use.	(If the filters are used)     Replace the filters.     Press and hold Timer key for more then 10 sec.     C letter will disappear.